

Front Coil-Over Conversions for A-Arms

Converting your stock A-arm front suspension to coil-over shocks is now a simple bolt-on procedure. VariShock pioneered the ball-stud pivot mount assembly to replace compliant rubber bushings with spherical-bearing precision and enable simple coil-over conversions using the factory upper shock-stem mount. The lower end of the shock uses a urethane-bushed or spherical-bearing eye, or urethane-bushed lower crossbar to mount directly to the factory or aftermarket lower A-arm, completing the simple and tidy installation.

VariShock coil-overs can easily be the "anything" solution. Five different travel lengths, ranging from 2.80" to 6.15", combined with standard- and short-length bases, and multiple lower mount styles create the broadest selection of A-arm coil-over conversion shocks and spring rates available from any manufacturer. Our compact base allows a much shorter collapsed shock length to free up more suspension travel. You can run softer springs with a stiffer anti-roll bar for better ride quality and handling, instead of extremely stiff

springs to control a short travel suspension.

Kits include shocks, springs, and mounting hardware with a second set of different rate springs, spanner wrench, and spring seat thrust bearings offered as options. All shock components and hardware are plated, anodized, or powder coated for a long-lasting quality appearance.

Fits various applications with lower A-arm mounted shock



Crossbar for use with factory A-arm



1/2" bearing eye for use with aftermarket A-arm

PART NUMBER	VALVING	LOWER MOUNT	TOTAL TRAVEL ¹	COLLAPSED LENGTH	EXTENDED LENGTH	RIDE-HEIGHT MINIMUM	RIDE-HEIGHT MAXIMUM	SPRING LENGTH	PRICE ² EACH
VAS 861M1-35	SINGLE	COM-8	3.50"	10.13"	13.63"	11.53"	12.23"	7"	\$279.00
VAS 861M1-43	SINGLE	COM-8	4.25"	10.88"	15.13"	12.58"	13.43"	9"	279.00
VAS 861MN-350	SINGLE	CROSSBAR ³	3.50"	9.63"	13.13"	11.03"	11.73"	7"	279.00
VAS 861MN-425	SINGLE	CROSSBAR ³	4.25"	10.38"	14.63"	12.08"	12.93"	9"	279.00
VAS 861MQ-425	SINGLE	1/2 EYE ⁴	4.25"	10.38"	14.63"	12.08"	12.93"	9"	279.00
VAS 861MR-35	SINGLE	COM-8	4.25"	9.63"	13.13"	11.03"	11.73"	7"	279.00
VAS 861MR-43	SINGLE	COM-8	4.25"	10.38"	14.63"	12.08"	12.93"	9"	279.00
VAS 862M1-35	DOUBLE	COM-8	3.50"	10.13"	13.63"	11.53"	12.23"	7"	394.00
VAS 862M1-43	DOUBLE	COM-8	4.25"	10.88"	15.13"	12.58"	13.43"	9"	394.00
VAS 862MN-350	DOUBLE	CROSSBAR ³	3.50"	9.63"	13.13"	11.03"	11.73"	7"	394.00
VAS 862MN-425	DOUBLE	CROSSBAR ³	4.25"	10.38"	14.63"	12.08"	12.93"	9"	394.00
VAS 862MQ-425	DOUBLE	1/2 EYE ⁴	4.25"	10.38"	14.63"	12.08"	12.93"	9"	394.00
VAS 8621MR-35	DOUBLE	COM-8	4.25"	9.63"	13.13"	11.03"	11.73"	7"	394.00
VAS 862MR-43	DOUBLE	COM-8	4.25"	10.38"	14.63"	12.08"	12.93"	9"	394.00
OPTION	SECOND SET OF DIFFERENT RATE SPRINGS FOR TUNING								100.00

NOTES 1 - 2.80, 3.50, 4.25, 5.15 AND 6.15" TRAVEL LENGTHS ARE AVAILABLE WITH MANY MORE LOWER MOUNT STYLES (BEARING OR CROSSBAR) BY SPECIAL ORDER.

2 - SOLD IN PAIRS UNLESS OTHERWISE NOTED

3 - CROSSBAR IS FOR USE OEM-STYLE CONTROL ARM MOUNT

4 - 1/2" -EYE IS FOR USE WITH AFTERMARKET CONTROL ARM CLEVIS MOUNT