

6232

INSTRUCTIONS FOR MILD STEEL AND 4130 ROD ENDS

<u>ITEM</u>	<u>QTY</u>	<u>PART NO.</u>	<u>DESCRIPTION</u>
1	2	3305	3/4 X 3/4 mild steel right (2 piece, narrow body)
2	2	3306	3/4 x 3/4 mild steel left (2 piece, narrow body)
3	2	3307	3/4 x 3/4 4130 right (3 piece, wide body)
4	2	3308	3/4 x 3/4 4130 left (3 piece, wide body)

1. Determine which rod ends are 4130; they are the 3 piece rod ends with the wide heavy body around the ball. The top bars will be pulled apart, putting greater strain on the rod ends, therefore, the 4130 rod ends should be used in the top bars.

2. The mild steel, 2 piece rod ends, have a narrow body around the ball. Use them in the bottom bars because the bars will be pushed together.

Revision Date: May 31, 2007



6232

INSTRUCTIONS FOR MILD STEEL AND 4130 ROD ENDS

<u>ITEM</u>	<u>QTY</u>	<u>PART NO.</u>	<u>DESCRIPTION</u>
1	2	3305	3/4 X 3/4 mild steel right (2 piece, narrow body)
2	2	3306	3/4 x 3/4 mild steel left (2 piece, narrow body)
3	2	3307	3/4 x 3/4 4130 right (3 piece, wide body)
4	2	3308	3/4 x 3/4 4130 left (3 piece, wide body)

1. Determine which rod ends are 4130; they are the 3 piece rod ends with the wide heavy body around the ball. The top bars will be pulled apart, putting greater strain on the rod ends, therefore, the 4130 rod ends should be used in the top bars.

2. The mild steel, 2 piece rod ends, have a narrow body around the ball. Use them in the bottom bars because the bars will be pushed together.

Revision Date: May 31, 2007

