

**6301****INSTRUCTIONS FOR STOCK FLOOR SEAT MOUNT**

<u>ITEM</u>	<u>QTY</u>	<u>PART NO.</u>	<u>DESCRIPTION</u>
1	4	2316	Seat brackets - stock floor
2	4	3108	Bolt 1/4 - 28 x 3/4
3	4	3211	Locknut 1/4 - 28

This bracket set is designed to bolt to the threaded bosses in the bottom of most after market seats.

1. Position the seat in the car in the correct location per the driver's preference.
2. Two of the brackets bolt to the bottom of the seat, one on each side. The brackets will have to be drilled to bolt to the bottom of the seat.
3. The other two brackets bolt to the stock floor (hardware not provided). Be sure to use large washers under all bolts and nuts that attach the brackets to the seat and floor. The brackets have 6 mounting holes on each side, only one front and one rear location need to be used to bolt the brackets together. The combinations available will allow you to adjust for many different heights and angles. If none of them fit your application, you can drill your own holes. Use the 1/4 bolts and locknuts provided to bolt the brackets together.
4. You will need to attach the back of the seat to the crossbar in your roll cage. A flat plate weld to the crossbar can be bolted to the outer layer of the seat, just below the headrest.

Revision Date: June 27, 2003

